







COMPACT CARS

PARKING ANGLE	WIDTH AT CURB	SINGLE LOADED AISLES		DOUBLE LOADED AISLES	
		ONE-WAY TRAFFIC	TWO-WAY TRAFFIC	ONE-WAY TRAFFIC	TWO-WAY TRAFFIC
					
BAY WIDTH * (feet)					
30°	16.01	26.0	34.0	40.0	48.2
32.5°	14.90	26.5	34.4	40.9	49.1
35°	13.95	26.8	34.7	41.8	49.8
37.5°	13.15	27.3	35.2	42.6	50.5
40°	12.45	27.6	35.5	43.2	50.9
42.5°	11.85	27.8	35.8	43.6	51.5
45°	11.32	28.2	36.3	44.3	52.1
47.5°	10.85	29.0	36.5	45.4	52.6
50°	10.45	29.8	36.8	46.4	52.9
52.5°	10.09	30.5	37.2	47.2	53.3
55°	9.77	31.3	37.3	48.0	53.6
57.5°	9.49	31.9	37.7	48.6	53.8
60°	9.24	32.7	37.9	49.3	54.1
62.5°	9.02	33.3	38.2	50.0	54.3
65°	8.83	33.9	38.4	50.8	54.5
67.5°	8.66	34.6	38.8	51.3	54.7
70°	8.52	35.2	38.9	51.8	54.8
72.5°	8.39	35.8	39.2	52.3	54.8
75°	8.28	36.5	39.3	52.8	54.9
77.5°	8.20	37.2	39.6	53.3	55.1
80°	8.12	37.8	39.8	53.9	55.2
82.5°	8.07	38.3	39.9	54.3	55.3
85°	8.03	39.0	40.1	54.7	55.3
87.5°	8.01	39.7	40.2	55.0	55.3
90°	8.00	40.3	40.3	55.3	55.3

Use of Compact Spaces requires approval of an exception by the Community Development Director or the Architectural Review Commission. Compact spaces are allowed only if justified by unusual circumstances such as saving a tree or using otherwise unusable space.

Bay widths are based on 16' stall lengths and 8' stall widths. A maximum of 40% of the stalls in a parking lot may be compact. (In residential apartment projects involving ten or more units, 50% of spaces may be compact.)

Compact parking spaces shall be clustered.

* See ENG. STANDARD #2220 for clarification of "BAY WIDTH"

REVISIONS	BY	APP	DATE
<i>New border</i>	<i>JDL</i>	<i>WAP</i>	<i>1-98</i>
<i>Rearrange</i>	<i>RMH</i>	<i>WAP</i>	<i>1-95</i>
STANDARD CURRENT AS OF: January 2010			



PARKING BAY DIMENSIONS COMPACT CARS